SHERPA 100/\CROL



TECHNICAL DATA SHERPA 100 AGRI

Motor

Manufacturer Honda Type GX390

Capacity 8,7/11,7 kW/hp
Revolutions per minute 3600 rpm
Adjusted amount of revolutions 3000 rpm

Number of cylinders

Cooling Air Cooled
Fuel Petrol (Euro95)

Fuel tank capacity 6,1 l

Drive system Hydrostatic on 2 rear wheels/ 2 front wheels

through chain transmission

Speed 0-5 (proportional) km/h*

Capacity data

Breakout force 690 kg
Tractive force 370 kg*

Hydraulic drive- and working system 18 l/min - 190 bar

Hydraulic tank capacity 38 l

Tires


Standard 4.00x10 - traction profile tires

Brakes

Braking system Hydrostatic on 2 rear wheels/ 2 front wl

through chain transmission

Steering Skid steering



A Maximum height with bucket up	2545	J Bucket angle high	53°
B Height hinge point coupling plate	2050	K Wheelbase	657
C Maximum height with bucket low	1220	L Length to coupling plate	1520
D Length + bucket	2165	M Ground clearance	121
E Bucket angle when dumping	51°	N Rear Angle	14°
F Height underside of the bucket when dumping	1480	O Turning radius	1606
G Length from front wheel to bucket when dumping	180	P Turning radius with bucket	2250
H Height bucket horizontally	1860	Q Width	760
I Haak bak laan	2/0		





TECHNICAL DATA SHERPA 100 AGRI

Max. Dimensions (L mm x B mm x H mm, without bucket):

Standard 1520 x 760 x 1220


Kerb weight 539 kg (with standard tires)

Tipping loads (kg)*:

Pallet forks low**

A 179 B 260 C 476

Pallet forks high**



A 129

* Including driver 75kg ** Consider a safety factor of 30%

SHERPA 100 AGRI

Thanks to the width of only 76 cm, the SHERPA 100 Agri-Line can pass through narrow passages. This makes it an ideal machine for work at riding schools and in the stables. The SHERPA 100 Agri-line is a welcome aid for the mucking out.

More information? Call us +31 412 61 33 44

Canadabaan 14 | 5388 RT Nistelrode | www.sherpaminiloaders.com







