SHERPA 10PETROL





TECHNICAL DATA SHERPA 100 PETROL

Motor

Manufacturer Honda GX630 Type

Capacity 15/21 kW/hp Revolutions per minute 3600 rpm Adjusted amount of revolutions 2650 rpm

Number of cylinders

Cooling Air cooled Petrol (Euro95) Fuel

Fuel tank capacity 16 L

Drive system Hydrostatic through 2 hydraulic wheel motors

Speed 315 cc wheelmotor 0-8 (proportional) km/h* Speed 400 cc wheelmotor 0-7 (proportional) km/h*

Capacity data

Breakout force 630 kg Tractive force 315 cc wheelmotors 220 kg* 330 kg* Tractive force 400 cc wheelmotors Hydraulic drive- and working system 29/190 l/bar

Hydraulic tank capacity 45 l

Tires Standard 20x11.00-8 - Trac profile tires wide Narrow 4.00-10 - Trac profile tires small

Brakes

Braking system Hydrostatic on 2 rear wheels/ 2 front wheels

through chain transmission

Steering Skid steering

Dimensions in mm on standard tyres

| A Maximum height with bucket up | 2600 | J Bucket angle high | 53° |
|--|------|------------------------------|------|
| B Height hinge point coupling plate | 2105 | K Wheelbase | 657 |
| C Maximum height with bucket low | 1250 | L Length to coupling plate | 1508 |
| D Length + bucket | 2112 | M Ground clearance | 176 |
| E Bucket angle when dumping | 51° | N Rear Angle | 23° |
| F Height underside of the bucket when dumping | 1560 | O Turning radius | 1690 |
| G Length from front wheel to bucket when dumping | 60 | P Turning radius with bucket | 2265 |
| H Height bucket horizontally | 1930 | Q Width | 1140 |
| I Bucket angle low | 26° | | |





TECHNICAL DATA SHERPA 100 PETROL

Electrical system

Voltage 12 V Battery capacity 45 Ah

Max. Dimensions (L mm x B mm x H mm, without bucket):

 Standard
 1490 x 1140 x 1218

 Narrow
 1490 x 860 x 1218


Kerb weight 642 kg (with standard tires)

B 341

C 625

Tipping loads (kg)*:

Pallet forks low**



Pallet forks high**
A 234



- * Including driver 60kg
- ** Consider a safety factor of 30%

SHERPA 100 PETROL

Notable is the powerful and reliable Honda petrol engine of 21 hp that ensures that the SHERPA 100 Petrol stands his ground during the most challenging work. Whether it is dragging tree trunks, moving concrete tiles or sand.

More information? Call us +31 412 61 33 44

Canadabaan 14 | 5388 RT Nistelrode | www.sherpaminiloaders.com

