SHERPA S10





TECHNICAL DATA SHERPA S10

Motor

Driving capacity 40/55 kW / hp Capacity hydraulics 7.5/10 Kw / hp Adjusted amount of revolutions 3000 rpm

Drive system 4 electric wheel motors

Max. speed Turtle 0-7 (proportional) km/h* Max. speed Hare 0-15 (proportional) km/h*

Capacity data Turtle Hare Breakout force 590 kg 590 kg Tractive force 1100 kg* 1100 kg* Werkhydrauliek 25 l/150 bar 25 l/150 bar 24 l Hydraulic tank capacity


Tires


Standard 5.70x12 Wide 24x13.00-12NHS

Brakes Braking system Electric Service brake Electric

Articulated steering Steering 45°

Steering angle





Dimensions in mm on standard tyres

A Maximum height with bucket up	2490	J Bucket angle high	38°
B Height hinge point coupling plate	2190	K Wheelbase	1187
C Maximum height with bucket low	1290	L Length to coupling plate	2310
D Length + bucket	2960	M Ground clearance	255
E Bucket angle when dumping	38°	N Rear Angle	42°
F Height underside of the bucket when dumping	1640	O Turning radius	2195
G Length from front wheel to bucket when dumping	685	P Turning radius with bucket	2335
H Height bucket horizontally	1985	Q Width	760
I Bucket angle low	31°	R Height ROPS	2210
		R Height ROPS folded	1610





TECHNICAL DATA SHERPA \$10

Oscillating system

Oscillating angle 17

Turning circle Anticlockwise 4460; Clockwise 4140

Electrical system

Voltage 96 V

Battery capacity 18/27 Kwh

Dimensions (L mm x B mm x H mm, without bucket):


 Standard
 2359 x 760 x 2218


 Wide
 2359 x 1112 x 2218

Kerb weight 1050 kg (incl. counterballast of 47kg &

standard tires)

Tipping loads (kg)*:





- * Including driver 60kg
- ** Consider a safety factor of 30%

SHERPA S10

The perfect articulated loader for smaller spaces! The S10 is based on the SHERPA 150, but is fully electric and even more powerful. This machine is equipped with a strong yet maintenance-free lithiumion battery, that has a particularly long lifespan. Therefore the S10 can be used for a full workday! The machine also has hydraulic quick lock and an even higher tractive force than the SHERPA 150. Finally, the S10 is only 76 centimetres wide when fitted with the standard tyres.

More information? Call us +31 412 61 33 44

Canadabaan 14 | 5388 RT Nistelrode | www.sherpaminiloaders.com







